

**For Any Technical Questions, Please Contact at [info@nodesus.com](mailto:info@nodesus.com)**

**Product Name:**FX Dehumidifier

**Part Number:** FX-CS400A, CS-500B, CS-1000A

**Product Description:**

Smart size easy to move,Ultra-quiet operation,keep your room dry and comfortable.

**FX-CS400A:**

Thermoelectric Dehumidifier, With Button Control, 1.5L water tank, dehumidification capacity 408ML/D (at RT 30°C, 80%RH), input power:56W, Noise level <45dB with water full indicator light , Working ambient temperature :15-32C.ETL report

**CS-500B:**

Thermoelectric Dehumidifier, With Touch screen Control, 750ml water tank, dehumidification capacity 500ML/D (at RT 30°C, 80%RH), input power:55W, Noise level <45dB with water full indicator light , Working ambient temperature :15-32C , ETL report

**CS-1000A:**

**For Any Technical Questions, Please Contact at [info@nodesus.com](mailto:info@nodesus.com)**  
Thermoelectric Dehumidifier, With Touch screen Control, 1.7 water tank, dehumidification capacity 1000ML/D (at RT 30°C, 80%RH), input power:105W, Noise level <45dB with water full indicator light , Working ambient temperature :15-32C, Air purification function, purificate PM 2.5, ETL report under process.

**Product Specification:**

Model	FX-CS400A
Picture	 A white, rectangular thermoelectric dehumidifier. The front panel features a circular control knob at the top and a vertical water level indicator window at the bottom. The right side of the unit has a dark, textured grille, likely for air intake or output. The device is shown against a plain white background.

For Any Technical Questions, Please Contact at [info@nodesus.com](mailto:info@nodesus.com)

Specification	<p>Dehumidifying Quantity: 400ML/D(30°C, RH=80%)</p> <p>Unit Dimension: W20.7*D14.1*H33.5cm</p> <p>Packing Dimension: W26*D19.5*H41.2cm</p> <p>Power Input: 55w</p> <p>Power Interface: Built-in power panel</p> <p>Water Tank Capacity: 1500ML</p> <p>Use Temperature: 15-40°C</p> <p>Noise: &lt;45db</p> <p>NW/GW: 2kg/2.8kg</p>
---------------	--

Model	CS-500B
Picture	 The image shows two identical cylindrical dehumidifiers. Each has a white top section and a dark grey or black bottom section. The bottom section features a vertical ribbed texture. The dehumidifier on the right has a black power cord extending from its base. The background is white with a faint watermark.

For Any Technical Questions, Please Contact at [info@nodesus.com](mailto:info@nodesus.com)

Specification	<p>Dehumidifying Quantity: 400ML/D(30°C, RH=80%)</p> <p>Unit Dimension: W17.4*D17.4*H29.5cm</p> <p>Packing Dimension: W22.8*D22.5*H35.2cm</p> <p>Power Input: 50w</p> <p>Power Interface: Built-in power panel</p> <p>Water Tank Capacity: 750ML</p> <p>Use Temperature: 15-40°C</p> <p>Noise: &lt;45db</p> <p>NW/GW: 1.8/2.3kg</p>
---------------	---

Model	CS-1000A
Picture	

**For Any Technical Questions, Please Contact at [info@nodesus.com](mailto:info@nodesus.com)**

Specification	<p>Dehumidifying Quantity: 800ML/D(30°C, RH=80%)</p> <p>Unit Dimension: W23*D23*H35.5cm</p> <p>Packing Dimension: W28.8*D29.1*H42.3cm</p> <p>Power Input: 100w</p> <p>Power Interface: Built-in power panel</p> <p>Water Tank Capacity: 1800ML</p> <p>Use Temperature: 15-40°C</p> <p>Noise: &lt;55db</p> <p>NW/GW: 2.1/3kg</p>
---------------	---

