



# GRIPS /

## MAIN FEATURES

Shape is tough, with clear layers and fine leather appearance; Elastic soft rubber, soft and comfortable feel, strong grip, non-slip, sweat away; Easy installation and disassembly, no need for strong disassembly;



### T430.T430/2 /

/Approval	RoHS
/Size	L136mm W34mm H34mm
/Weight	99g
/Material	TPR
/Fitting Depth	116mm



/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	3.9N.m
/Torsional Strength	≥9N.m



### T428.T428/2 /

/Approval	RoHS
/Size	L136mm W34mm H34mm
/Weight	99g
/Material	TPR
/Fitting Depth	116mm



/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	≥3.9N.m
/Torsional Strength	≥9N.m



### T406.T406/2 /

/Approval	RoHS
/Size	L136mm W34mm H34mm
/Weight	99g
/Material	TPR
/Fitting Depth	116mm



/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	3.9N.m
/Torsional Strength	≥9N.m



### T392.T392/2 /

/Approval	RoHS
/Size	L117mm H34mm
/Weight	90g
/Material	TPR
/Fitting Depth	107mm



/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	3.9N.m
/Torsional Strength	≥9N.m



### T390.T390/2 /

/Approval	RoHS
/Size	L117mm H34mm
/Weight	55g
/Material	TPR
/Fitting Depth	107mm



/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	≥3.9N.m
/Torsional Strength	≥9N.m



### T376.T375. HT375 /

/Approval	RoHS
/Size	L118mm W50mm H33mm
/Weight	58.5g/46.3g/17.1g
/Material	PVC




/Fitting Depth	1375/175mm/1376/114mm
/Operating Temperature	-20°C~ 60°C
/Pulling-out Force	≥150N



### T380.T382 /


/Approval	RoHS
/Size	L130mm W54.6mm H35.5mm
/Weight	44.3g
/Material	TPR

	
/Fitting Depth	[T380]124mm,[T382]79mm
/Operating Temperature	-20°C~60°C
/Pulling-out Force	≥150N



### T462 /

/Approval	RoHS
/Size	L118.2mm W34.6mm H34.6mm
/Weight	100g
/Material	PVC

	
/Fitting Depth	111mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥200N



### T460 /

/Approval	RoHS
/Size	L120mm W33mm H33mm
/Weight	120g
/Material	PP+TPR
/Fitting Depth	114mm

	
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	≥3.9N.m
/Torsional Strength	≥9N.m



### T450 /


/Approval	RoHS
/Size	L115mm W33mm H33mm
/Weight	62g
/Material	PP+TPR
/Fitting Depth	111mm

	
/Operating Temperature	-20°C~60°C
/Pulling-out Force	≥400N
/Locking Torque	3.9N.m
/Torsional Strength	≥9N.m



### T426 /


/Approval	RoHS
/Size	L113mm W34mm H34mm
/Weight	/
/Material	PVC

	
/Fitting Depth	103mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T416+DG517 /

/Approval	RoHS
/Size	L132mm W33mm H36.8mm
/Weight	46.3g
/Material	PVC

	
/Fitting Depth	110mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T432 /

/Approval	RoHS
/Size	L114mm W34mm H34mm
/Weight	80g
/Material	TPR

/Fitting Depth	106mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T418 /

/Approval	RoHS
/Size	L114mm W33mm H33mm
/Weight	46.3g
/Material	PVC

/Fitting Depth	110mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T438 /

/Approval	RoHS
/Size	L116mm W34mm H34mm
/Weight	46.3g
/Material	TPR

/Fitting Depth	108mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T535 /

/Size	L124.5mm W34mm H34mm
/Weight	98.9g
/Material	PVC

/Fitting Depth	120mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T581 /

/Size	L114.5mm W33mm H33mm
/Weight	78.8g
/Material	PVC

/Fitting Depth	109mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T605 /

/Size	L115mm W34mm H34mm
/Weight	75g
/Material	PVC

/Fitting Depth	108mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T525+DG557/1 /

/Size	L128.5mm W34mm H34mm	/Operating Temperature	-20°C ~ 60°C
/Weight	21.2g+46.8g	/Pulling-out Force	>400N
/Material	ABS+PVC	/Locking Torque	≤3.5N.m
/Fitting Depth	110mm	/Torsional Strength	≤7N.m



### T420 /

/Approval	RoHS	/Fitting Depth	123mm
/Size	L128mm W34mm H34mm	/Operating Temperature	-20°C ~ 60°C
/Weight	46.3g	/Pulling-out Force	≥150N
/Material	TPR		



### T611 /

/Size	L115mm W33mm H33mm	/Fitting Depth	110mm
/Weight	84g	/Operating Temperature	-20°C ~ 60°C
/Material	PVC	/Pulling-out Force	≥150N



### T110 /

/Size	L106mm H31mm	/Fitting Depth	102mm
/Weight	45.3g	/Operating Temperature	-20°C ~ 60°C
/Material	PVC	/Pulling-out Force	≥150N



### T609 /

/Size	L115mm W33mm H33mm	/Fitting Depth	110mm
/Weight	84g	/Operating Temperature	-20°C ~ 60°C
/Material	PVC	/Pulling-out Force	≥150N



### T386 /

/Approval	RoHS	/Fitting Depth	107mm
/Size	L118mm W34mm H34mm	/Operating Temperature	-20°C ~ 60°C
/Weight	/	/Pulling-out Force	≥150N
/Material	PVC		





### T247 /

/Approval	RoHS
/Size	L112mm W31mm
/Weight	46.3g
/Material	PVC

/Fitting Depth	108mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T246 /

/Approval	RoHS
/Size	L67mm W31mm
/Weight	46.3g
/Material	PVC

/Fitting Depth	62mm
/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥150N



### T388.HT388 /

/Approval	RoHS
/Size	L70mm H34mm/L116mm H34mm
/Weight	35g/55g
/Material	TPR
/Fitting Depth	[T388]60mm

/Operating Temperature	-20°C ~ 60°C
/Pulling-out Force	≥400N
/Locking Torque	3.9N.m
/Torsional Strength	≥9N.m

