

## Dual Platform Split Type Hot Bar Welding Machine



### Parameter

Item	Specification
Model	SD-HB01-C
Input Voltage	AC220V±5V
Power Supply Frequency	50/60HZ
Cooling	Air Cooling
Working Pressure	4-6KG
Power	800-2000VA
Heating Time	0.1-999S
Current	4-8A
Working Environment Temperature	-10°C-60°C
Working Environment Humidity	20-90%
HMI	7 Inch Touch Panel Screen
Dimension(WxDxH mm)	800*600*600
Packing Size	900*700*700
Weight	60Kg

## Integrated Hot Bar Welding Machine



### Parameter

Item	Specification
Model	SD-HB03-C
Input Voltage	AC220V±5V
Power Supply Frequency	50/60HZ
Cooling	Air Cooling
Working Pressure	4-6KG
Power	800-2000VA
Heating Time	0.1-999S
Current	4-8A
Working Environment Temperature	-10°C -60°C
Working Environment Humidity	20-90%
HMI	7 Inch Touch Panel Screen
Dimension(WxDxH mm)	600*400*600
Packing Size	700*500*850
Weight	50Kg

# Dual Platform Integrated Hot Bar Welding Machine



## Parameter

Item	Specification
Model	SD-HB02-C
Input Voltage	AC220V±5V
Power Supply Frequency	50/60HZ
Cooling	Air Cooling
Working Pressure	4-6KG
Power	800-2000VA
Heating Time	0.1-999S
Current	4-8A
Working Environment Temperature	-10°C -60°C
Working Environment Humidity	20-90%
HMI	7 Inch Touch Panel Screen
Dimension(WxDxH mm)	600*650*700
Packing Size	650*700*800
Weight	75Kg

# Double Side Welding Machine



## Parameter

Item	Specification
Model	SD-HBSM-SD
Input Voltage	AC220V±5V
Power Supply Frequency	50/60HZ
Cooling	Air Cooling
Working Pressure	4-6KG
Power	4000-6000VA
Heating Time	0.1-999S
Current	10-15A
Working Environment Temperature	-10°C-60°C
Working Environment Humidity	20-90%
HMI	7 Inch Touch Panel Screen
Dimension(WxDxH mm)	800*600*1400
Packing Size	900*700*1500
Weight	75Kg