



SWITCHES /

MAIN FEATURES

Simple structure, reliable process and stable performance ; Clamping aluminum alloy locking ring, more stable ; Ergonomic operation, light and comfortable ; Achieve IPX4 waterproof capacity ; Environmentally friendly materials, RoHS certification.



DK16 /

/Approval	RoHS
/Size	L65mm W28mm H39mm
/Weight	23g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	2/3 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK138 /

/Approval	RoHS
/Size	L136.5mm W46mm H55mm
/Weight	100g
/Waterproof	IPX4
/Material	PC/ABS TPR

/Wiring	2 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥60N
/Durability	100,000 mating cycle



DK136 /

/Approval	RoHS
/Size	L39mm W61mm H22mm
/Weight	21g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	2 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK226 /

/Approval	RoHS
/Size	L142mm W22mm H42mm
/Weight	100g
/Waterproof	IPX4
/Material	PP TPR

/Wiring	3/4 Pins
/Current	0.5A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK138/2 /

/Approval	RoHS
/Size	L20mm W46mm H54mm
/Weight	21g
/Waterproof	IPX4
/Material	PA6+GF20

/Wiring	2 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥60N
/Durability	100,000 mating cycle



DK226/2 /

/Approval	RoHS
/Size	L22mm W50mm H42mm
/Weight	32g
/Waterproof	IPX4
/Material	PA6+20GF TPR

/Wiring	3 /4 Pins
/Current	0.5A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle





DK218 /

/Approval	RoHS
/Size	L61mm W37mm H38mm
/Weight	26g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	4 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



NEW



DK252 /

/Approval	RoHS
/Size	L61mm W37mm H38mm
/Weight	26g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	4 Pins
/Current	50mA/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK216 /

/Approval	RoHS
/Size	L66mm W42mm H39mm
/Weight	34g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	4 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK242 /

/Approval	RoHS
/Size	L45mm W22mm H50mm
/Weight	36.8g
/Waterproof	IPX4
/Material	PA6+20GF TPR

/Wiring	3 Pins
/Current	50mA/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



采用内侧走线方式
THE INNER WIRING METHOD CAN BE USED



DK256 /

/Approval	RoHS
/Size	L60mm W62mm H25mm
/Weight	40g
/Waterproof	IPX4
/Material	ABS

/Wiring	5 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle



DK336 /

/Approval	RoHS
/Size	L147mm W54mm H54mm
/Weight	110g
/Waterproof	IPX4
/Material	PP TPR

/Wiring	8 Pins
/Current	0.5A/12V DC
/Operating Temperature	-20°C~60°C
/Wire Tension	≥130N
/Durability	100,000 mating cycle





DK224 /

/Approval	RoHS
/Size	L73mm W55mm H33mm
/Weight	37g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	4 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~ 60°C
/Wire Tension	>130N
/Durability	>100,000 times



DK240 /

/Approval	RoHS
/Size	L33mm W55mm H72mm
/Weight	38g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	4 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~ 60°C
/Wire Tension	>130N
/Durability	100,000 mating cycle



DK214 /

/Approval	RoHS
/Size	L34.5mm W54.2mm H66.8mm
/Waterproof	IPX4
/Material	PC/ABS
/Wiring	4 Pins

/Current	3A/12V DC
/Operating Temperature	-20°C~ 60°C
/Wire Tension	>130N
/Durability	100,000 mating cycle



DK336/2 /

/Approval	RoHS
/Size	L26mm W54mm H54mm
/Weight	41g
/Waterproof	IPX4
/Material	PA6+20GF TPR

/Wiring	6/8 Pins
/Current	0.5A/12V DC
/Operating Temperature	-20°C ~ 60°C
/Wire Tension	>130N
/Durability	100,000 mating cycle



DK324 /

/Approval	RoHS
/Size	L80mm W32mm H55mm
/Weight	43g
/Waterproof	IPX4
/Material	PC/ABS

/Wiring	7 Pins
/Current	3A/12V DC
/Operating Temperature	-20°C~ 60°C
/Wire Tension	>130N
/Durability	100,000 mating cycle



DK314 /

/Approval	RoHS
/Size	L34.5mm W54.2mm H79.6mm
/Waterproof	IPX4
/Material	PC/ABS
/Wiring	7 Pins

/Current	3A/12V DC
/Operating Temperature	-20°C~ 60°C
/Wire Tension	>130N
/Durability	100,000 mating cycle





DK340 /

/Approval	RoHS	/Wiring	2 Pins
/Size	L39mm W61mm H22mm	/Current	3A/12V DC
/Weight	17.7g	/Operating Temperature	-20°C ~ 60°C
/Waterproof	IPX5	/Wire Tension	≥130N
/Material	PC/ABS	/Durability	100,000 mating cycle



DK412 /

/Approval	RoHS	/Wiring	7 Pins
/Size	L66mm W68mm H33mm	/Current	3A/12V DC
/Weight	75g	/Operating Temperature	-20°C ~ 60°C
/Waterproof	IPX4	/Wire Tension	≥130N
/Material	ABS	/Durability	100,000 mating cycle



DK410 /

/Approval	RoHS	/Current	3A/12V DC
/Size	L85mm W35mm H57mm	/Operating Temperature	-20°C ~ 60°C
/Waterproof	IPX4	/Wire Tension	≥130N
/Material	PC/ABS	/Durability	100,000 mating cycle
/Wiring	9 Pins		

